



TITAN Cement Company S.A. 22A, Chalkidos str.1143 Athens, Greece  
15

**EN 12004**

**Normal setting cementitious adhesive with reduced slip and extended open time, for internal and external tiling (C1TE): Sterea  
DoP: INTERMIX No 25**

<b>Reaction to fire</b>	Class A1
<b>Release of dangerous substances</b>	See MSDS
<b>Bond strength as :</b>	
-initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
<b>Durability for :</b>	
-tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$
-tensile adhesion strength after water immersion	$\geq 0,5 \text{ N/mm}^2$
-tensile adhesion strength after freeze/thaw cycles	$\geq 0,5 \text{ N/mm}^2$



TITAN Cement Company S.A. 22A, Chalkidos str.1143 Athens, Greece  
15

**EN 12004**

Improved cementitious adhesive with reduced slip and extended open time, for  
internal and external tiling (C2TE): Sterea Pro

DoP: INTERMIX No 26

Reaction to fire	Class A1
Release of dangerous substances	See MSDS
<b>Bond strength as :</b>	
- -initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
<b>Durability for :</b>	
-tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$
-tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$
-tensile adhesion strength after freeze/thaw cycles	$\geq 1,0 \text{ N/mm}^2$



TITAN Cement Company S.A. 22A, Chalkidos str.1143 Athens, Greece  
15

**EN 12004**

**Improved deformable cementitious adhesive with reduced slip and extended open time, for internal and external tiling (C2TE S1): Sterea Flex**

**DoP: INTERMIX No 27**

<b>Reaction to fire</b>	Class A1
<b>Release of dangerous substances</b>	See MSDS
<b>Bond strength as :</b>	
-initial tensile adhesion strength	≥1,0 N/mm <sup>2</sup>
<b>Durability for :</b>	
-tensile adhesion strength after heat ageing	≥1,0 N/mm <sup>2</sup>
-tensile adhesion strength after water immersion	≥1,0 N/mm <sup>2</sup>
-tensile adhesion strength after freeze/thaw cycles	≥1,0 N/mm <sup>2</sup>