



# **ThermaBond Plus - White**

**Cementitious Adhesive & Base-Coat Mortar  
for Thermal Insulation Boards**

Declaration of Performance

**INTERMIX 36**

Elefsina Plant



## Declaration of Performance INTERMIX 36

1. Unique identification code of the product-type:  
**ThermaBond Plus - White**
2. Intended use or uses:  
**General purpose rendering/plastering mortar for external and internal use (GP)**
3. Manufacturer:  
**TITAN Cement SA, 22A Halkidos Str., 111 43, Athens, Greece**
4. System/s of AVCP:  
**System 4**
5. Harmonised standard:  
**EN 998-1:2016**
6. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Euroclass A1	EN 998-1:2016
Capillary water absorption	W <sub>c</sub> 2	
Water vapour permeability coefficient (μ)	μ≤15	
Adhesion	≥0,6 N/mm <sup>2</sup> FP: B	
Thermal conductivity (λ <sub>10,dry</sub> )	0,61 W/mK	
Durability	NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Production & Port Manager, Quality Control  
Manager & Environmental Engineer



Konstantinos Vertsonis  
Elefsina, 31/10/2024