



ThermaBond Ultra

Cementitious Adhesive & Base-Coat Mortar
for Thermal Insulation Boards

Declaration of Performance

INTERMIX 37

Elefsina Plant



Declaration of Performance INTERMIX 37

1. Unique identification code of the product-type:
ThermaBond Ultra
2. Intended use or uses:
General purpose rendering/plastering mortar for external and internal use (GP)
3. Manufacturer:
TITAN Cement SA, 22A Halkidos Str., 111 43, Athens, Greece
4. System/s of AVCP:
System 4
5. Harmonised standard:
EN 998-1:2016
6. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Euroclass A1	EN 998-1:2016
Capillary water absorption	W _c 2	
Water vapour permeability coefficient (μ)	μ≤15	
Adhesion	≥0,6 N/mm ² FP: B	
Thermal conductivity (λ _{10,dry})	0,61 W/mK	
Durability	NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Production & Port Manager, Quality Control
Manager & Environmental Engineer



Konstantinos Vertsonis
Elefsina, 31/10/2024